


STP100D-12/TFA




25-YEAR WARRANTY



for IEC Certified Module


ELECTRICAL CHARACTERISTICS

Open-Circuit Voltage (Voc)	22.3 V
Optimum Operating Voltage (Vmp)	17.5 V
Short-Circuit Current (Isc)	5.91 A
Optimum Operating Current (Imp)	5.72 A
Maximum Power at STC* (Pmax)	100 Wp
Operating Temperature	-40°C to +85°C
Maximum System Voltage	1000 V
Maximum Series Fuse Rating	15 A
Power Tolerance	±5 %
Nominal Voltage	12V



MECHANICAL CHARACTERISTICS

Solar Cell	Polycrystalline
No. of Cells	36 (4×9)
Dimensions (mm/inch)	1131×676×35mm / 44.6×12.0×0.7
Weight (kg/lbs)	9.4 Kgs / 20.7 lbs
Junction Box	IP65 rated
Output Cables (mm/inch)	Symmetrical lengths (-) 750/29.5 and (+) 750/29.5
Wind Loads	H4 connector 2400 Pascal
Snow Loads	5400 Pascal



TEMP. CHARACTERISTICS

Nominal Operating Cell Temperature (NOCT)**	45±2°C
Temp. coefficient of Pmax	-0.47 %/°C
Temp. coefficient of Voc	-0.34 %/°C
Temp. coefficient of Isc	0.045 %/°C

*STC: Irradiance 1000W/m², module temperature 25°C, AM=1.5
 **NOCT: Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s